

(2) 東莞樹脂ガイド

RG シリーズ

規格表

RG

規格名称	D	L (mm)	L1 (mm)	使用ボルト	F (mm)	適用規格ばね
RG 23-050	23	50	38	M 12 X 65X P=1.75	27	TL50・TM50 TH50・TB50
RG 23-075		75	63	M 12 X 90X P=1.75		
RG 23-100		100	88	M 12 X115X P=1.75		
RG 23-125		125	113	M 12 X140 X P=1.75		
RG 26-050	26	50	38	M 12 X 65X P=1.75	27	TF50
RG 26-075		75	63	M 12 X 90 X P=1.75		
RG 26-100		100	88	M 12 X115X P=1.75		
RG 26-125		125	113	M 12 X140 X P=1.75		
RG 28-050	28	50	38	M 12 X 65X P=1.75	27	TL60・TM60 TH60・TB60
RG 28-075		75	63	M 12 X 90 X P=1.75		
RG 28-100		100	88	M 12 X115X P=1.75		
RG 28-125		125	113	M 12 X140 X P=1.75		
RG 31-050	31	50	38	M 12 X 65X P=1.75	27	TF60
RG 31-075		75	63	M 12 X 90 X P=1.75		
RG 31-100		100	88	M 12 X115X P=1.75		
RG 31-125		125	113	M 12 X140 X P=1.75		
RG 36-050	36	50	38	M 12 X 65X P=1.75	27	TF70・TL70・TM70 TH70・TB70
RG 36-075		75	63	M 12 X 90 X P=1.75		
RG 36-100		100	88	M 12 X115X P=1.75		
RG 36-125		125	113	M 12 X140 X P=1.75		